

CLAMCO HEAT SHRINK TUNNELS

Quality-designed dependable performers, our 7221 and 6022 tunnels are the ideal choices for use with 6700 Series Sleeve Wrappers.

MODEL 7221 Production Shrink Tunnel

Standard Features

- Chamber area 46" L x 22" W x 10" H
- Digitally controlled heat to 450°; variable air velocity control
- 14,500 watts heating power; adjustable pattern; 220V
- Separate conveyor 20" W x 71" L; speed 0-125 fpm
- Fully insulated chamber; double entry/exit curtains
- Air-cooled controls
- Sturdy steel base with casters
- Silicone-covered roller conveyor (rotating or nonrotating)
- Conveyor cooling fan
- Overall dimensions: 71" L x 37" W x 67" H

Options: Additional rollers, fiberglass mesh or stainless-steel mesh conveyor, stainless-steel construction, spare parts kit



Model 7221 Production Shrink Tunnel

MODEL 6022 Heat Shrink Tunnel

Standard Features

- Chamber area size up to 34" L x 22" W x 10" H
- 9,000 watts heating power, 220V, single phase
- Variable-speed 60"-long quick-adjusting live/dead silicone roller conveyor with 1.5" spacing
- Digital precision temperature control; automatic cool-down
- Heavy-duty console with levelers
- Overall dimensions: 60"

Options: 1" roller spacing, mesh belt overlay, variable air velocity, locking casters, 208V3 phase



Model 6022 Production Shrink Tunnel

Distributor:

CLAMCO
CORPORATION

Your **one** source for packaging systems since 1946

12900 Plaza Drive Cleveland, OH 44130
1-800-299-1655 216-267-1911
Fax 216-267-8713
www.clamcocorp.com
e-mail: info@clamcocorp.com

One or more of the following U.S. Patents apply: 5,372,494; 5,381,640; 5,423,162; 5,842,320.
Specifications and design features subject to change without notice. Some photos may show accessories not part of basic machine.
Printed in U.S.A. © 2007 Clamco Corp.

CLAMCO
CORPORATION

Your **one** source for packaging systems since 1946



6700 SERIES

**AUTOMATIC
L-BAR
SEALERS**

